

# Protex 5200 / 520gsm PVC- FR

## Gloss- 152cm & 205cm



Red  
152cm & 205cm



White  
152 & 205cm



Dark green  
152cm only



Grey  
152 & 205cm



Blue  
152 & 205cm



Yellow  
152cm only



Black  
152cm only



Green  
152cm only

Base fabric: 460 Decitex Woven Polyester 64gsm  
 Coating: Laminate of Flexible PVC on each side of scrim fabric  
 Total mass: 520gsm (+/- 25) Thickness: 0.43mm  
 Finish: Gloss  
 Roll length: 50m  
 Roll width: 150cm & 205cm

### Physical properties tested in accordance with BS 3424 "Methods of test for coated fabrics"

TENSILE STRENGTH: Warp 930 N/50mm  
 Part 4, Method 6 Weft 930 N/50mm

FLAMIBILITY: Complies with BS5867 Part 2  
 Type A when Tested by  
 BS5438 Test 3

TEAR STRENGTH: Across Warp 290N  
 Part 5 Method 7B Across Waft 250N

WATER PENETRATION: Min.1500mm

COATING ADHESION: 25N/50mm  
 Part 7 Method 9B

CHEMICAL RESISTANCE: Satisfactory

COLD CRACK: Not higher than -25°C  
 Part 8 Method 10A

FLEX RESISTANCE: 5000,000 flexes minimum to  
 Part 9 Method 11B meet the requirements of ISO  
 7854 1984 (Method B)

Conforms with BS3408/20

DECABROMODIPHENYL ETHER (DECABDE) FREE

COLOUR FASTNESS: 4/5 (7 being the highest)

REACH: Complies with regulation (EC) No. 1907/2006 concerning REACH- Test period March 2014

[www.mitco.co.uk](http://www.mitco.co.uk)

tel. 0141 773 5469

email. info@mitco.co.uk