

PROTEX 5800 / 580gsm PVC FR

Matt / 152cm & 205cm



Black
152 & 205cm




Red
152 & 205cm



White
152 & 205cm



Orange
152cm



Translucent
152cm



Green
152cm



Olive
152 & 205cm



Brown
152cm



Grey
152 & 205cm



Dk Blue
152 & 205cm



Cream
152cm

Base fabric: 550 Decitex, Woven polyester 77 gms
 Coating: Laminate of Flexible PVC on each side of fabric
 Total mass: 580 gsm Thickness: 0.48mm
 Finish: Matt
 Roll length: 50m
 Roll widths: 152cm & 205cm

Physical properties tested in accordance with BS 3424 "Methods of test for coated fabrics"

TENSILE STRENGTH: Warp 1000 N / 50mm
 Part 4, Method 6 Weft 1400 N / 50mm

FLAMIBILITY: Complies with BS5867 Part 2
 Type A and B when Tested by
 BS5438 Test 2

COATING ADHESION: 30N / 50mm
 Part 7 Method 9B

WATER PENETRATION: Min. 1500 mm
 CHEMICAL RESISTANCE: Generally

COLD CRACK: Not lower than -25°C
 HEAT RESISTANCE: Not higher than +70°C
 Part 8 Method 10A

FLEX RESISTANCE: 500,000 flexes minimum to
 Part 9 Method 11B meet the requirements of ISO
 7854 1984 (Method B)

LIGHT TRANSMITTANCE: 43.7% (on Translucent)

COLOUR FASTNESS: 4/5 (7 being the highest)

DECABROMODIPHENYL ETHER (DECABDE) FREE

Conforms with BS3408/20

REACH: Complies with regulation (EC) No. 1907/2006 concerning REACH
 Test period March 2014

www.mitco.co.uk

tel. 0141 773 5469

email. info@mitco.co.uk