

PROTEX 610gsm PVC, Fluorescent / FWR / Lacquered- 152cm

(code: 610152/FloOraLaq/J)



Fluorescent Orange / white

Base fabric: 1100 Decitex, Woven polyester 184 gms
Coating: Tough and flexible coating of polyvinyl chloride, both sides
Total mass: 610 gsm
Finish: Lacquered
Roll length: 35m

Physical properties tested in accordance with BS 3424 "Methods of test for coated fabrics"

FLAMIBILITY: Complies with BS5867 Part 2 Type A and B when Tested by BS5438 Test 2

TENSILE STRENGTH: Warp 2450 N / 50mm FUSION: Pass
Part 4, Method 6 Weft 2000 N / 50mm Part 22, Method 25A

TEAR STRENGTH: Across Warp 500N WATER PENETRATION: Minimum 1500 mm
Part 5 Method 7B Across Weft 400N

COATING ADHESION: 120N / 50mm CHEMICAL RESISTANCE: Generally
Part 7 Method 9B

COLD CRACK: Not lower than -20°C FLEX RESISTANCE: 500,000 flexes minimum to
Part 8 Method 10A Part 9 Method 11B requirements of ISO 7854 1984

These are typical results intended for guidance only.

Conforms with BS3408/20

www.mitco.co.uk

tel. 0141 773 5469

email. info@mitco.co.uk