

PROTEX 6100 / 610gsm PVC, Fluorescent Fire Retardant- 152cm (code: WH-P-FR-3)



Fluorescent Orange / white

Base fabric:	1100 Decitex, Woven polyester 184 gms
Coating:	Tough and flexible coating of polyvinyl chloride, both sides
Total mass:	610 gsm
Finish:	Lacquered
Roll length:	50m

Physical properties tested in accordance with BS 3424 "Methods of test for coated fabrics"

FLAMIBILITY:	Complies with BS5867 Part 2 Type A and B when Tested by BS5438 Test 2		
TENSILE STRENGTH:	Warp 2450 N / 50mm	FUSION:	Pass
Part 4, Method 6	Weft 2000 N / 50mm	Part 22, Method 25A	
TEAR STRENGTH:	Across Warp 500N	WATER PENETRATION:	Minimum 1500 mm
Part 5 Method 7B	Across Weft 400N		
COATING ADHESION:	120N / 50mm	CHEMICAL RESISTANCE:	Generally
Part 7 Method 9B			
ANTI UV TREATMENT		ABRASION TESTED:	100N/5cm
COLD CRACK:	Not lower than -30°C	FLEX RESISTANCE:	500,000 flexes minimum to
Part 8 Method 10A		Part 9 Method 11B	requirements of ISO 7854 1984

These are typical results intended for guidance only.

Conforms with BS3408/20

REACH: Complies with regulation (EC) No. 1907/2006 concerning REACH
Test period March 2014
DECABROMODIPHENYL ETHER (DECABDE) FREE

www.mitco.co.uk

tel. 0141 773 5469

email. info@mitco.co.uk