

MITCO Industrial Textiles  
15 Dunivaig Road  
Easter Queenslie Industrial Estate  
Glasgow  
G33 4TT



**TECHNICAL DATA**

**CLEAR WINDOW PVC SHEETING- 0.50mm Fire Retardant**

**Verification: J- 20.11.14**

Raw material	PVC
Thickness	.50mm / 20 Thou
Tensile strength	Warp- 190kg / cm2 Weft- 180kg / cm2
Tear strength	Warp- 6kg / mm Weft- 6kg / mm
Elongation (%)	Warp- 240% Weft- 280%
Heat shrinkage (%)	Warp- minus 5 Weft- plus 2
Cold crack	Not lower than - 20 degrees C
UV Resistance	Yes – 0.2 / hr
Fire retardant	Yes (BS7837:1996, BS5438:1998, test method 2B)

DECABROMODIPHENYL ETHER (DECABDE) FREE

REACH: Complies with regulation (EC) No. 1907/2006 concerning REACH- Test period  
March 2014

Width	137cm
Weight	640g / m2
Roll length	50m

REMARKS: (1) Commodity contains vinyl chloride monomer below 10 P.P.M.  
(2) PHR means Per Hundred parts Ratio.  
(2) U.V.I. Means Ultra Violet Inhibition.