

# HYTEX 1500 / R15 Canvas FWR or SDC

Cotton / Canvas- Flame, Rot & Waterproof



Green		
	FWR	SDC
91cm	✓	✓
183cm	✓	

White	
FWR	SDC
✓	

Olive	
FWR	SDC
	✓

Base fabric:	Cotton canvas
Finish:	Closed selvedge
Weight:	14oz/yd <sup>2</sup> - 509gms/m <sup>2</sup> (+/- 5)
Width:	91 cm
Roll length:	approx. 80 to 100 m

PHYSICAL PROPERTY	SPEC.	TOL	TEST METHOD
Bath test- leakage (mls)	Nil	-	Internal
Bath test- Absorbtion (%)	16 max	-	Internal
Crushed cone test- leakage (mls)	Nil	-	BS 3408: 1992
Cone test- Absorbtion (%)	Nil	-	"
Hydrostatic head tested (10cm / min)	18		ISO 811
Flammability- bottom edge	pass	-	BS 7837 (BS 5438 2B)
Flammability (after soaking)- bottom edge	pass	-	BS 7837/BS 5651
Colour fastness, dry rub / wet rub	3 / 3	-	ISO 105 X 12 BS 1006 X 12
Rotproof content	Pass	-	BS 2087 PT2- 6.5 METH. 5
Spray rating	3		ISO 4920 BS EN24920
Tensile Strength, Warp	1300	-	EN ISO 13934-1
Tensile Strength, Weft	1100		"
Wing Rip Tear, Warp	35	-	EN ISO 13937-1
Wing Rip Tear, Weft	30	-	"

[www.mitco.co.uk](http://www.mitco.co.uk)

tel. 0141 773 5469

email. [info@mitco.co.uk](mailto:info@mitco.co.uk)