

# HYTEX RM12 FWR or SDC- 91cm

Cotton / Canvas- Flame, Rot & Water proof



White  
(FWR & SDC)



Green  
(SDC only)

Base fabric:	Cotton canvas
Finish:	Closed selvedge
Weight:	12oz/yd <sup>2</sup> - 407gms/m <sup>2</sup> (+/- 5)
Width:	91 cm
Roll length:	approx. 80 to 100 m

PHYSICAL PROPERTY	SPEC.	TOL	TEST METHOD
Bath test- leakage (mls)	Nil	-	Internal
Bath test- Absorbtion (%)	16 max	-	Internal
Crushed cone test- leakage (mls)	Nil	-	Def Stand. 83-27 lss
Cone test- Absorbtion (%)	Nil	-	"
Dimensional change- Warp / Weft	2.5 / 2.5	+/-1	ISO 7771 BS 4736
Hydrostatic head tested (10cm / min)	60		ISO 811
Flammability- bottom edge	pass	-	BS 7837 (BS 5438 2B)
Flammability (after soaking)- bottom edge	pass	-	BS 7837/BS 5651
Rotproof content	Pass	-	BS 2087 PT2- 6.5 METH. 5
Spray rating	3		ISO 4920 BS EN24920
Tensile Strength, Warp / Weft	1500 / 1000		EN ISO 13934-1
Wing Rip Tear, Warp / Weft	35 / 30	-	EN ISO 13937-3

tel. 0141 773 5469

fax. 0141 773 5455

email. info@mitco.co.uk

[www.mitco.co.uk](http://www.mitco.co.uk)