

Lyntex 1200 / 12oz Plain Weave FR

Polyester / Cotton Canvas- Flame, Rot & Water proof



White (94&200cm)



Sand (200cm only)



Forest (200cm only)

Base fabric:	Polyester / cotton
Composition:	52% polyester / 48% cotton
Weight:	12oz/yd ² - 407gms/m ² (+/- 5)
Roll widths:	94 & 200cm
Roll length:	approx. 50 to 100m (94cm) / 50 to 70m (200cm)

PHYSICAL PROPERTY	SPEC.	TOL	TEST METHOD
Bath test- leakage (mls)	Nil	-	Internal
Bath test- Absorbtion (%)	16 max	-	Internal
Crushed cone test- leakage (mls)	Nil	-	DEFSTAN83-27
Cone test- Absorbtion (%)	nIL		"
Hydrostatic head	exceeds 400mm		
Spray rating	80		ISO4920 / BSEN 24920
Colour fastness / dry rub	3	-	BSEN ISO105:X12
Colour fastness / wet rub	4	-	"
Light fastness	6+	-	BSEN ISO105:B02
Tensile Strength, Warp (N)	1800	-	BSEN ISO22286
Tensile Strength, Weft (N)	1500	-	"
Flame retardant	Yes		BS7837:1996 (2015)

www.mitco.co.uk