

PROTEX 5800 / 580gsm PVC FR

Matt / 152cm & 205cm



Black

152 / 205cm



Red

152 / 205cm




White

152 / 205cm



Orange

152cm



Translucent

152cm



Dk Green

152 / 205cm



Olive

152 / 205cm



Brown

152cm



Grey

152 / 205cm



Dk Blue

152 / 205cm



Cream

152cm

Base fabric: 550 Decitex, Woven polyester 77 gms
Coating: Laminate of Flexible PVC on each side of fabric
Total mass: 580 gsm Thickness: 0.48mm
Finish: Matt
Roll length: 50m
Roll widths: 152cm & 205cm

Physical properties tested in accordance with BS 3424 "Methods of test for coated fabrics"

TENSILE STRENGTH: Warp 1000 N / 50mm
Part 4, Method 6 Weft 1400 N / 50mm

FLAMIBILITY: Complies with BS5867 Part 2
Type A and B when Tested by
BS5438 Test 2

COATING ADHESION: 30N / 50mm
Part 7 Method 9B

WATER PENETRATION: Min. 1500 mm
CHEMICAL RESISTANCE: Generally

COLD CRACK: Not lower than -25°C
HEAT RESISTANCE: Not higher than +70°C
Part 8 Method 10A

FLEX RESISTANCE: 500,000 flexes minimum to
Part 9 Method 11B meet the requirements of
ISO 7854 1984 (Method B)

LIGHT TRANSMITTANCE: 43.7% (on Translucent)

COLOUR FASTNESS: 4/5 (7 being the highest)

DECABROMODIPHENYL ETHER (DECABDE) FREE

Conforms with BS3408/20

REACH: Complies with regulation (EC) No. 1907/2006 concerning REACH
Test period March 2014

www.mitco.co.uk

tel. 0141 773 5469

email. info@mitco.co.uk